

Date of Issue: 13 March 2000 Revision: 4 ID: tmin

TRIMETHYLINDIUM

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY.

Product Name Trimethylindium

Formula (CH₃)₃In Company Identification See footer.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Preparation Trimethylindium Components/Impurities None EC No. 222-200-9

CAS No. 3385-78-2

3. HAZARDS IDENTIFICATION

Pyrophoric solid, decomposes violently in water. Skin contact can cause severe burns. Fumes may cause skin and eye irritation. Avoid inhalation of fumes. Trimethylindium is thermally unstable above $140^{\circ}C - DO$ NOT HEAT ABOVE $80^{\circ}C$

4. FIRST AID MEASURES

Prompt medical attention is required in all cases of exposure to Trimethylindium and its by-products. Rescue personnel should be equipped with appropriate protective equipment (e.g. Self-contained breathing apparatus) to prevent unnecessary exposure and must be aware of the fire and explosion potential of Trimethylindium.

Skin

Contact may cause severe burns. Fumes may cause irritation. Immediately flush affected areas with large quantities of water. Remove affected clothing as rapidly as possible only is not stuck to skin.

Eyes

Contact may cause severe burns. Fumes may cause irritation. Persons with potential exposure to Trimethylindium should not wear contact lenses. Flush contaminated eyes with large quantities of water for at least 15 minutes. Hold eyelids open to ensure complete flushing.

Inhalation

May cause irritation. Move exposed personnel to an uncontaminated area quickly using self-contained breathing apparatus. If breathing is difficult, give oxygen. If breathing has stopped, apply artificial respiration. Medical assistance should be sought immediately. Keep victim warm and quiet.

MATERIAL SAFETY DATA SHEET

5. FIRE-FIGHTING MEASURES

Extinguishing Media

Always use dry powder, soda ash or lime. Never use water, foam or halogenated compounds to fight fires involving organometallic materials. Without risk, stop flow of this compound to the fire. Without risk, and if safe to do so, move container(s) away from fire area.

Exposure Hazards

In a controlled fire any unreacted Trimethylindium may re-ignite when contact with air or water is renewed.

Special Protective Equipment for Fire-Fighters

Fire resistant clothing, self-contained breathing apparatus, face shield and safety goggles, safety shoes and fire resistant gloves.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Evacuate area. Use appropriate protective equipment. Purge equipment with inert gas before attempting repairs. Ensure adequate ventilation. If leak is in container call one of the emergency numbers as appropriate (See footer). **Environmental Precautions** Try to stop release, if safe to do so. For fire-fighting measures see Section 5.

Clean up methods

Contact Epichem for specific advice.

7. HANDLING AND STORAGE

Handling

Valve outlet seals must remain in place unless container is secured and valve outlet piped to use point. Use a check valve or trap to prevent hazardous back flow into the container. Any equipment used for Trimethylindium service must be thoroughly cleaned and prepared to eliminate contamination and must be maintained in a leak-free state. All air and moisture in the system must be eliminated before use.

Storage

Protect containers from physical damage. Do not allow temperatures to exceed (125F)51C. Store away from flammable material.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Controls

OSHA or ACGIH:

TLV(TWA)= 0.1 mg/m³ (In and compounds) **OEL and MEL:** Long term exposure limit for Indium and compounds: 0.1mg/m³ (as In) (8-Hour TWA reference period) Short term exposure limit: 0.3 mg/m³ (15-Minute reference period) Ensure adequate ventilation.

Personal Protection

Self-contained breathing apparatus, fire resistant gloves, face shield and safety goggles, safety shoes, fire-resistant garments. Safety shower and eyewash.



9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: (272.8F)133.8C Vapor Pressure: log₁₀ P(mmHg) = 10.52 - 3014/T(K) Melting Point: (191F) 88C Molecular Weight: 159.93 grams Density: Crystal density= 1.568 (literature) Powder density= 1.3 (experimental) Solubility in water: Reacts violently. Appearance: White solid which is pyrophoric.

10. STABILITY AND REACTIVITY

Conditions to avoid

Reacts pyrophorically in air. *Note:* Trimethylindium is stable indefinitely in an inert atmosphere at room temperature. **THERMALLY UNSTABLE ABOVE 140°C. DO NOT HEAT ABOVE 80°C. Materials to avoid** Avoid water, air or other oxidizers. **Hazardous Decomposition Products** Indium Oxide dust, CO, CO₂

11. TOXICOLOGICAL INFORMATION

Indium Oxide dust formed when this compound is oxidized is an irritant to skin, eyes and by inhalation.

Trimethylindium is not listed in the IARC, NTP or OSHA Subpart Z as a carcinogen or potential carcinogen.

Trimethyindium is listed on the TSCA inventory.

12. ECOLOGICAL INFORMATION

This product does not contain any Class I or Class II ozone depleting chemicals.

13. DISPOSAL CONSIDERATIONS

Regional and National regulations should be followed during waste disposal. Contact an Epichem representative for disposal of container and any unused quantities.

14. TRANSPORT INFORMATION

UN No: 2846 CLASS: 4.2 PG I ECCN#: 3C003 IMDG Code: 4255 Shipping Name: Pyrophoric solid, organic, n.o.s. (Trimethylindium)

15. REGULATORY INFORMATION

Classification Highly Flammable Risk and Safety Phrases R14: Reacts violently with water. R17: Spontaneously flammable in air. S6: Keep under inert atmosphere. S8: Keep container dry. S43a: In case of fire use dry powder or lime - Never use water.

16. OTHER INFORMATION

Ensure operators understand the pyrophoric and potentially thermally unstable nature of the product. DSC data available on request. Before using this product, it is recommended that a risk assessment and safety study be carried out. Further information on the use of this product can be obtained from the Technical Product Manager at the nearest Epichem facility.

SAFETY NOTICE: In Order to provide our customers with the highest quality material and maintain our high standards of safety, the surface temperature of the bubbler will be monitored during the transportation of our products. We would like to monitor the surface temperature of the bubbler using a tempilabel. Tempilabel is a temperature-monitoring strip ranging from 120F to 150F (49C to 66C) which will indicate the temperature during shipment. The strip will turn black at one of the four ratings shown if the temperature is reached (normally a silver centre). If the temperature monitor is changed, please notify an Epichem representative immediately and we will assist you in the proper measures to be taken. We ask for your co-operation in our efforts of quality assurance and safety. If you have any questions or comments, please contact an Epichem representative. We thank you for your co-operation. Your assistance is greatly appreciated.

Information contained in this material safety data sheet is offered without charge for use by technically qualified personnel at their discretion and risk. All statements, technical information and recommendations contained herein are based on tests and data which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed no warranty of any kind is made with respect thereto. This information is not intended as a license to operate under or a recommendation to practice or infringe any patent of this Company or others covering any process, composition of matter or use.

Since the Company shall have no control of the use of the product described herein, the company assumes no liability for loss or damage incurred from the proper or improper use of such product.

EPICHEM LIMITED POWER ROAD, BROMBOROUGH WIRRAL, MERSEYSIDE, CH62 3QF, U.K. Tel: 44 (0) 151 334 2774 Fax: 44 (0) 151 334 6422 EPICHEM INCORPORATED 26 WARD HILL AVE, PO BOX 8230 HAVERHILL, MA, 01835, USA Tel: 1 508 374 5200 Fax: 1 508 374 6474

24 Hour Emergency Contact Numbers: Europe: 44 151 334 2774 United States: Chemtrec: (800) 424 9300 Other International Countries: Chemtrec (703) 527 3887